



VKW FRONTBESEN



SCAN ME

VKW FRONTBESEN

The specially developed front broom VKW can easily be mounted frontally on a **DIN plate of type A or type B** can be mounted.

Depending on the requirements, **the front broom can be mounted on chassis of various brands** such as Volvo, Scania, MAN, Mercedes.

We offer **different sizes depending on the type of milling machine** and customer's requirements.

Simple operation by joystick in the cabin. The front broom is driven hydraulically.

STANDARD

- Heavy duty steel structure with rounded sheet steel protection
- Specially developed suspension with Form feed
- Mounting plate for quick installation
- Integrated hydraulic motor with a capacity of 400 ccm.
- Hydraulic hoses for pressure return with leak-proof quick couplings
- Two height-adjustable heavy-duty support wheels with a diameter of 280 mm
- Fully protected hydraulic Valve block
- 2x lifting cylinders
- 1x cylinder for form feed
- 2x cylinders for the hydraulic
- Tilt adjustment of the front brush
- Proportional speed control can be operated from the cab.
- Independent automatic pressure control of the front brushes.
- Lubrication points on all moving parts

TECHNICAL SPECIFICATIONS

	VKW 200	VKW 235
Working width	1.960 mm	2.350 mm
Total width	2.260 mm	2.650 mm
Diameter	800 mm	800 mm
Hydromotor		
Side shift 250 mm	0 - 250 mm	0 - 250 mm
Proportional speed control	Standard	Standard
Hydraulic floating position	Standard	Standard
Hydraulic group on the front broom	Standard	Standard
Hydraulic group on the sweeper	Optional	Optional
2x leak-proof quick couplings	Standard	Standard
Faster Hydraulic Quick Coupling	Optional	Optional
Height-adjustable support wheels	Standard	Standard
Extra reinforced support wheels	Optional	Optional
Side marking lights LED	Standard	Standard
2-pole plug for the side marker light	Standard	Standard
16-pin plug for the control	Standard	Standard



Technical modifications reserved. All information without guarantee. Product photos may contain additional equipment.